

- Stainless Steel Case
- Copper Alloy Wetted Parts
- Glycerine Filled or Dry/Fillable
- Convenient Panel Mounting Adapters

### Specifications

**Case:** Stainless Steel

**Ring:** Stainless Steel Crimped or Bayonet

**Lens:** Bayonet style - Glass

Crimped style - Plastic (1.5", 4")

Note: \*Some 2.5" crimped items may be shipped with plastic lens

**Dial:** Aluminum,  
Black Figures on White Background

**Wetted Parts:** Copper Alloy w/ restrictor screw

**Temperature:** 0° to 150°F

**Accuracy:** 1.6% Full Scale (All Bayonet & 4" crimped)  
3-2-3% (1.5", 2.5" crimped)

### Applications

The PG Gauge is an economical choice where ambient corrosion and vibration are of concern. Its stainless steel case and ring offer excellent corrosion resistance, and the PG is fillable for vibration or pulsation applications. Suitable for all fluids compatible with copper alloys.



## HOW TO ORDER

PG — 25 — C — 2 — A — 4 — P23 — G

Dial:	Case:	Tube & Socket:	Mounting:	Connection:	Range Code:	Filling:
15 = 1.5" 25 = 2.5" 35 = 3.5" 40 = 4"	<b>C</b> = Stainless Steel Crimped Ring, (1.5", 2.5", 4") Plastic Lens (all sizes) <b>S</b> = Stainless Steel, Bayonet Ring (2.5", 3.5", 4")	<b>2</b> = Copper Alloy	<b>A</b> =  Bottom (All) <b>B</b> =  Bottom/Rear Flange (2.5", 3.5", 4") <b>C</b> =  Back (2.5", 1.5") (4") <b>D</b> = Back /"U" or "O" Clamp  (4")  (1.5", 2.5") <b>E</b> =  Back/Fr. Flange (2.5", 1.5") (4")	<b>8</b> = 1/8" NPT (1.5", 2.5") <b>4</b> = 1/4" NPT (2.5", 3.5", 4") <b>2</b> = 1/2" NPT (4")	<b>See Page 12 for Range Codes</b> <b>Available Ranges:</b> Vacuum compound, and 15 PSI to 6,000 PSI (Higher Ranges Available on Request)  • Peak Indicator (2.5" & 4" with "S" case) • Electrical Contacts (4" with "S" case)	<b>D</b> = Dry (Fillable) <b>G</b> = Glycerine  Other fills on request.  <b>Options:</b> • Custom / Logo Dials • Removed Restrictor Screw • Chemical Seals • Alternate lenses available