

SERIES PM

REOTEMP PRESSURE PRODUCTS

INDUSTRIAL STAINLESS STEEL GAUGES



- Stainless Steel Case and Crimped Ring
- Stainless Steel Wetted Parts
- Glycerine Filled or Dry/Fillable

Specifications

Case: 304 Stainless Steel

Ring: Stainless Steel, Crimped

Lens: Plastic (1.5", 4")

Glass* (2.5")

*Some 2.5" crimped items may be shipped with plastic lens

Dial: Aluminum,

Black Figures on White Background

Wetted Parts: 316 St. Steel w/ restrictor screw

Accuracy: 1.6% Full Scale (4")










3-2-3% (1.5") 2-1.6-2% (2.5")

Applications

The PM Series features stainless steel tube, socket and case, making the gauge resistant to corrosion from both environment and media. Liquid filling is recommended for severe service. The economical and attractive crimp ring design, along with a variety of convenient panel mounting adapters, make this popular gauge the right choice for many applications.

HOW TO ORDER

PM — **25** — **C** — **1** — **A** — **4** — **P23** — **G**

Dial:	Case:	Tube & Socket:	Mounting:	Connection:	Range Code:	Filling:
15 = 1.5" 25 = 2.5" 40 = 4"	C = 304 St. Steel, Crimped Ring	1 = 316 St. Steel	A =  Bottom (1.5", 2.5", 4") B =  Bottom/Rear Flange (2.5", 4") C =  Back (2.5")  (1.5") D =  Back "U" or "O" Clamp (2.5")  (1.5") E =  Back/Front Flange (2.5")  (1.5") F =  Bottom/Front Flange (2.5")	4 = 1/4" NPT (1.5", 2.5", 4") 2 = 1/2" NPT (4") 8 = 1/8" NPT (1.5", 2.5" optional)	See Page 12 for Range Codes Available Ranges: All ranges from vacuum 8,000 PSI Options: • Custom / Logo Dials • Chemical Seals • Alternate lenses available	D = Dry (Fillable) G = Glycerine Other fills on request.